

# NEW

# SILVERCUT DISC 1500 T FC

A high-capacity mowing combination, with up to 22.5 h/ha capacity, represents our response to the increased requirements of the highly professional users. The five separate cutting units equipped with hydro-pneumatic suspension provide perfect contour following even at high speeds. The mower combination attached to the existing tractor importantly reduces the investment and production costs in comparison to the self-propelled solutions.

CSS (Hydraulic collision safety system)

Hydraulically adjustable mowing height

Hydraulic float (hydro-pneumatic suspension)

Suspended chassis with steering axle

QCS (quick change system)

DDSS (disc drive safety system)



## TECHNICAL DATA

## SILVERCUT DISC 1500 T FC

Working width (m)	14,55
Number of discs	32 (4x8)
Number of blades	64
Blade dimensions (mm)	110x48x4
Discs rotation speed (rpm)	3000
PTO rotation speed (rpm)	1000
Weight (kg)	9100
Tractor power required (kW/HP)	258/350
Capacity (ha/h)	22,50*
Cutting height (mm)	40-70
Swath width (m)	1,60 - 3,00
Conditioner type	Finger
Discs rotation	paired
Transport width (m)	2,99
Transport height (m)	3,99
Transport length (m)	7,50

\* calculated at working speed of 15 km/h.



[www.sip.si](http://www.sip.si)

Robust hay harvesting